GUARDSMITH*

GUARDSMITH®

GUARDRAIL WORKSHEET

For Interior Guardrail

| Contact Name | |
|---------------------------|--|
| Company | |
| Address | |
| | |
| Phone | |
| Fax | |
| Email | |
| Zip Code of Destination _ | |

For a "Quick Quote" with freight charge FAX TO: 724-446-0988

| RAIL CONFIGURATIONS (please check) | | | | | | | | |
|------------------------------------|-----------------------------------------------|--|--|--|--|--|--|--|
| | Double Rail (D) 44" high, 42" to top of rail | | | | | | | |
| 0 0 | Single Rail (S) 18" high , 17" to top of rail | | | | | | | |
| | Lift-Out Brackets (U) | | | | | | | |

Please sketch your layout below. Beside each rail, note dimension and mark "D" for Double rail, "S" for Single rail or "U" for Lift-Out bracket. Layout will be calculated with standard nominal rail lengths of 2, 3, 4, 5, 6, 7, 8, 9, or 10 feet. *Nominal rail length dimension is from center of post to center of post.* We will respond within one business day with job and freight pricing. Should you need assistance with the layout, please call 1-800-868-5438.

Guardsmith®

by Herwin, Inc.

FAX: 724-446-0988 EMAIL: sales@herwin.biz